


# DESSALATOR DC FREEDOM & AC CRUISE


## Quick Guide for regular use

### START-UP PROCEDURE



- 1 Make sure the hull valve for the watermaker is opened, the selection valve on the pre-filter is in the sea water position and turn the pressure regulator knob almost fully counter clockwise (towards the [-] position). Set the switch to ON.
- 2 Wait until only the YELLOW LED blinks. Slightly increase the pressure up to 8 o'clock on the pressure gauge using the regulator knob. Stay in this position for about one minute.
- 3 Then increase the pressure to 9 o'clock using the regulator knob. Stay in this position for about one minute.
- 4 Then increase the pressure to 11 o'clock using the regulator knob. Stay in this position for about one minute.
- 5 Now you can increase the pressure to the green zone on the pressure gauge. When the water quality LED lights up green, your water maker produces fresh water.

### SHUTDOWN PROCEDURE



- 6 Set the power switch to OFF, to stop the water maker.
- 7 Turn the knob pressure regulator almost fully counter clockwise (towards the [-] position).

This Quick Guide is intended only as a reminder for everyday use. Make sure you are familiar with the contents of the full manual before using your watermaker. See [www.dessalator.com](http://www.dessalator.com) or flash this QR code.



# DESSALATOR<sup>®</sup>

[www.dessalator.com](http://www.dessalator.com)

